


L'Armaturier des Grands Projets

DISTANCIERS TRIANGULAIRES

Hauteur	Colisage ml	Poids kg/ml
5	400	0,44
6	400	0,45
7	400	0,46
8	400	0,47
9	400	0,48
10	400	0,49
11	400	0,50
12	400	0,51
13	400	0,52
14	400	0,53
15	400	0,54
16	400	0,56
18	400	0,58
20	400	0,83
22	400	0,87
24	400	0,91
26	400	1,16



SteelPose Armatures

 **01.84.18.22.71**

 contact@steelpose-armatures.fr

 Chemin du Larris, 91150 Brières les Scelles

 <https://steelpose-armatures.fr/>

Ouvert
De 8H à 18H



SteelPose Armatures


SteelPose
Armatures

RONDS À BETON

HLE FE500-3 en barres

Diamètre en mm	Poids théorique en kg/ml	Section en cm ²
6	0,222	0,283
8	0,395	0,503
10	0,617	0,785
12	0,888	1,131
14	1,208	1,54
16	1,578	2,01
20	2,466	3,14
25	3,853	4,91
32	6,313	8,04
40	9,865	12,56

TREILLIS SOUDES DE STRUCTURE (NFA 35-024)

Type	Diamètre mm	Section cm ² /m	Mailles mm	Long ml Larg ml	kg/m ²	m ² /pc	Poids kg/pc	Colisage
RAF R	4,5	0,80	200	50,00	1,043	120,00	125,10	1
	4,5	0,53	300	2,40				
PAF R	4,5	0,80	200	3,60	1,042	8,64	9,00	100
	4,5	0,53	300	2,40				
RAF C	4,5	0,80	200	40,00	1,250	96,00	120,00	1
	4,5	0,80	200	2,40				
PAF C	4,5	0,80	200	3,60	1,250	8,64	10,80	100
	4,5	0,80	200	2,40				
PAF V	4,5	0,80	200	3,20	7,68	9,60	9,60	100
	4,5	0,99	160	2,40				

TREILLIS SOUDES DE STRUCTURE (NFA 35-016)

Type	Diamètre mm	Section cm ² /m	Mailles mm	Long ml Larg ml	kg/m ²	m ² /pc	Poids kg/pc	Colisage
PAF 10	5,5	1,19	200	4,20	1,870	10,08	18,85	70
	5,5	1,19	200	2,40				
ST20	6	1,88	150	6,00	2,487	14,40	35,81	40
	7	1,28	300	2,40				
ST25	7	2,57	150	6,00	3,020	14,40	43,49	40
	7	1,28	300	2,40				
	7	1,28	300	2,40				
ST35	7	3,85	100	6,00	4,026	14,40	57,98	30
	7	1,28	300	2,40				
ST50	8	5,03	100	6,00	5,267	14,40	75,84	20
	8	1,68	300	2,40				
ST60	9	6,36	100	6,00	6,986	14,40	100,30	16
	9	2,51	250	2,40				

TREILLIS SOUDES DE STRUCTURE (NFA 35-016)

Type	Diamètre mm	Section cm ² /m	Mailles mm	Long ml Larg ml	kg/m ²	m ² /pc	Poids kg/pc	Colisage
	8,0	2,51	200	2,40				
ST15C	6	1,42	100	4,00	2,220	9,60	21,31	70
	6	1,42	100	2,40				
ST25C	7	2,57	150	6,00	4,026	14,40	57,98	30
	7	2,57	150	2,40				
ST25C S	7	2,57	150	3,00	4,026	7,20	28,99	40
	7	2,57	150	2,40				
ST25 MI	7	2,57	150	3,00	4,026	5,70	23,26	40
	7	2,57	150	1,90				
ST40 C	7	3,85	100	6,00	6,04	14,40	86,98	20
	7	3,85	100	2,40				
ST50 C	8	5,03	100	6,00	7,9	14,40	113,76	15
	8	5,03	100	2,40				
ST65 C	9	6,36	100	6,00	9,98	14,40	143,71	10
	9	6,36	100	2,40				

POTEAUX

Type	Filants	Ecart trame en cm	Fil trame en cm	Colisage	Note
PP 8X8	4 HA 10	15	HA 5	30 él	
PP 10x10	4 HA 10	15	HA 5	30 él	
PP 10x15	4 HA 10	15	HA 5	30 él	
PP 15x15	4 HA 10	15	HA 5	20 él	